

Cummins Powered 220KVA / 180 KW Standby Rated Generator

ENGINE:

CUMMINS 6CTAA8.3G (200KVA PRIME POWER SEA LEVEL RATED)

Water cooled, direct injection, turbo charged, 6 cylinders, 8 Litre, 4 stroke, 1500 RPM diesel engine. Electronically governed. 65% Block Load.

ALTERNATOR:

MARATHON ELECTRIC MAGNA PLUS MP200 - 4

3 Phase and neutral, 400/230V, 50 Hz, brush less, IP21 enclosure, 1% voltage regulation at 1500 RPM, single bearing, Class H insulation with 10% overload facility to match engine standby rating.

DRIVE:

Flexible coupling with engine and alternator rigidly flanged together for true alignment and alternator rotor bolted directly to engine flywheel via flexi disc plates.

FRAME:

Simplex channel base with anti-vibration mounting between set and base. The simplex base includes the fuel tank designed for 10 - 12 hours duration / 600 litres.

CONTROL PANEL:

AMF (Automatic Mains Fail) with automatic transfer switch, controlled via a Lovato RGK60 digital controller.

ACCESSORIES:

Starter batteries (maintenance free type); water jacket heater and sound and weatherproof enclosure manufactured from mild steel.

PHYSICAL

SPECIFICATIONS:

Enclosed in Sound/Weatherproof Canopy:

(L) 4m x (W) 1.5m x (H) 1.7m and dry weight is 2900 kg's.

NOTES:

Set output at 0.8 PF 289 Amps at sea level.

Height above sea level and temperature affect outputs quoted.

Complete and ready to run and connections of load cables and or mains cables for AMF sets.