

Daewoo Powered 330KVA / 265 KW Generator

ENGINE:

DAEWOO P126TI-II

(300 KVA / 240KW PRIME POWER SEA LEVEL RATED)

Water cooled, direct injection, turbo charged, 6 cylinders, 8 Litre, 4 stroke, 1500 RPM diesel engine. Electronically governed. Engine outputs in accordance with ISO 3046 / BS5514 / DIN 6217. Single step load facility of 65% at Prime.

ALTERNATOR:

MARATHON ELECTRIC MP 260 – 300KVA

3 Phase and neutral, 400/230V, 50 Hz, brush less, IP21 enclosure, 1% voltage regulation at 1500 RPM, single bearing, Class H insulation with 10% overload facility to match engine standby rating.

DRIVE:

Flexible coupling with engine and alternator rigidly flanged together for true alignment and alternator rotor bolted directly to engine flywheel via flexi disc plates.

FRAME:

Simplex channel base with anti-vibration mounting between set and base. The simplex base includes the fuel tank designed for 10 - 12 hours duration / 1000 litres.

CONTROL PANEL:

AMF (Automatic Mains Fail) control panel.

ACCESSORIES:

Starter batteries (maintenance free type); water jacket heater and sound and weatherproof enclosure manufactured from mild steel.

PHYSICAL

SPECIFICATINS:

4.6m L x 2.5m W x 2.5m H and dry weight is 4500 kg's.

NOTES:

Set output at 0.8 PF 413 Amps at sea level.

Height above sea level and temperature affect outputs quoted.

Complete and ready to run except for dieseline in tank and connections of load cables and or mains cables for AMF sets.